

# 8 Core Fiber Optic Distribution Box

## Description

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTX communication network system. The fiber splicing, splitting, distribution can be done in this box and meanwhile it provides solid protection and management for the FTTX network building

## Features

- Total enclosed structure.
- Material: ABS, PC+ABS, wet-proof, water-proof, anti-aging, protection level up to IP65.
- Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution ... etc all in one.
- Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor, installation and easy maintenance.
- Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.



## Configuration

Material	Size	Max Capacity	Nos of PLC	Nos of Adaptor	Weight	Color
Strengthen ABS PC+ABS	A*B*C(mm) 240*125*50	Splice 8 Fibers (2trays,8 fiber/tray)	/	8pcs of SC(max)	0.44kg	White

## Packing List

PCS/CARTON	Gross Weight (Kg)	Net Weight (Kg)	Carton Size (cm)	Cbm (m <sup>3</sup> )
20	10	9	56*25*30	0.042

## Standard Accessories

- Screw: 4mm\*40mm 4pcs

- Expansion bolt: M6 4pcs
- Cable tie:3mm\*10mm 6pcs
- Heat-shrink sleeve:1.0mm\*3mm\*60mm 8pcs